,		Approved For Release 2004/07/05/16/12-ROPSOB	6728R000300090071-0ROUTING
	DATE	2034 Z 15 JUN 62 SECRET	3 6 25
1			
. 29	то	DIRECTOR	
25X1	FROM	λ^{\prime}	N.
	ACTIO	Nº DPD (1 2 3 4 5 6 7 8 9 1ø) / (1 2 3 4 5 6 7 8 9 1ø)	ROUTINE
	INFO	:S/C (11)	
		mwi A, M,	_
25X1 25X1		TOR 2253Z 15 JUN 62	IN 39432
23/(1	TO	INFO	CITE
25X1	1	NO	UMENT NO. 27
25X1		ATT NA CLA	DECLASSIFIED SS. CHANGED TO: TS S C T REVIEW SATE: 20 4
25X1		TUA	H: HR 73-2 e: 16-7-81 REVIEWER 25X1
25X	1	1. ON JUNE 14,	ECOMMENDED THE FOLLOWING:
25>	< 1	A. DRT CHAMBER AT NOT BE LENG	THENED. SYSTEMS DYNAMIC
,		RESOLUTION RUN TO COMPLETE QUALIFICATION	CAN BE ACCOMPLISHED BY USING
		SIMULATED RECOVERY SYSTEM WITH LITTLE OR	NO EFFECT ON FINAL RESULTS.
•		SE CONCURS WITH THIS VIEW.	
•	(,,	B. DIFFUSION PUMPS TO GIVE HAND VA	CUUM CAPADILITY FOR DRT SHOULD
		DE PROCURED. SE CONCURS WITH THIS VIEW.	
		2. REGARDING MIRRORS FOLLOWING COURS:	E OF ACTION SHOULD BE TAKEN:
		A. FINISH ONE MORE ALUMINUM MIRROR	WHICH WILL MAKE AVAILABLE A
	λ.	TOTAL NUMBER OF THREE.	
,		B. INITIATE IMMEDIATE ACTION TO MA	CHINE DOWN LARGE BERYLLIUM
25X1		DLANK AT FOR FIRST FLIGHT.	
		C. INITIATE ORDER TO PRODUCE FOUR	(4) MORE DERYLLIUM MIRRORS.
		SEVEN BLANKS SHOULD DE PROCURED.	
		SECRET	
		REPRODUCTION BY OTHER THAN THE ISSUING	DEFICE IS PROHIBITED. Copy No.

REPRODUCTION BY OTHER THAN THE ISSUING OFFICE IS PROHIBITED. CAPPROVED FOR Release 2004/07/07 : CIA-RDP66B00728R000300090071-0 NRO review(s) completed.

25X1	S L C R L 1	
· · · · [(IN 39432) PAGE TWO	
L	D. CERAMIC COATING STUDY PROPOSED SHOULD NOT BE UNBERTAKEN.	
NDO	3. IT WAS ALSO FOUND THAT IN RESIDUAL INVENTORY THERE IS A LENS	
NRO 25X1	ASSEMBLED BY THIS LENS IS OUT OF ALIGNMENT. IT IS	
25X1	STRONGLY RECOMMENDED THAT BE DIRECTED TO REFURBISH THIS LENS A	
	OLD AS SPARE.	
25X1	4. SPECIFICATION FOR PANORAMIC AND STELLAR/INDEX CAMERA	
-	SUBSYSTEMS IS APPROVED WITH FOLLOWING CHANGES:	
Ĺ	A. PARAGRAPH 3.8.1 LAST SENTENCE. CHANGE TO READ, "THE CAMERA	
	SHALL PRODUCE PHOTOGRAPHS WITH AN AWAR RESOLUTION OF 80 LINES/MM OR	
2	GREATER WHEN OPERATED UNDER SIMULATED FLIGHT CONDITION USING THE	
	DRT WITH MOVING 421 CONTRAST AIR FORCE TEST PATTERN AS BEFINED IN MIL	
•	STD-150. IT SHALL BE A DESIGN GOAL TO ACHIEVE 80 LINER/MM OR GREATER	
•	AT 2:1 CONTRAST.	
25X1	B. PARAGRAPH 2.1 LIST SPECIFICATION DEFINING MIRROR	
	MANUFACTURING TOLERANCES.	
	C. THE SPECIFICATION SHALL REFLECT THAT SCAN RATE SHALL BE	
	DETERMINABLE FROM FILM BATA TO AT LEAST 10 PERCENT ACCURACY.	
25X1	WORK STATEMENT BATED 12 JUNE IS APPROVED PROVIDING:	
	A. STATEMENT OF RECOGNITION OF ROLE OF SEATO IS INCLUDED UNDER	
	PARAGRAPHS RELATING TO PROGRAM MANAGEMENT.	
	B. CHANGES IN SCHEDULE OF BELIVERABLE ITEMS REFLECTED BY	
	PARAGRAPH 2 AND PARAGRAPH 3 ARE INCLUDED.	
	C. ADDITION OF THREE (3) HANDLING SLINGS TO BE DELIVERED TO	
	A/P IN SEPTEMBER AND OCTOBER 1962.	
	END OF MESSAGE	

S E C R E T Approved For Release 2004/07/07 : CIA-RDP66B00728R000300090071-0